



## DIN 7715-5 **STEFFCA**<sup>®</sup> STANDARD

				CLASS P1	CLASS P2	CLASS P3
DIMENSIONS IN MM				TOLERANCE IN MM	TOLERANCE IN MM	TOLERANCE I MM
	0	to	1,6	± 0,20	± 0,20	± 0,40
>	1,6	to	4	± 0,20	± 0,30	± 0,40
>	4	to	6,3	± 0,20	± 0,40	± 0,50
>	6,3	to	10	± 0,30	± 0,50	± 0,60
>	10	to	25	± 0,30	± 0,60	± 0,80
>	25	to	40	± 0,40	± 0,80	± 1,00
>	40	to	63	± 0,50	± 1,00	± 1,50
>	63	to	100	± 0,60	± 1,20	± 2,00
>	100	to	160	± 0,80	± 1,40	± 2,50
>	160	to	250	± 1,00	± 1,60	± 3,00
>	250	to	400	± 1,60	± 2,50	± 5,00
				TOLERANCE IN %	TOLERANCE IN %	TOLERANCE IN %
>	400			± 0,50	± 0,80	± 1,50

© Steffca A/S 2021

This document was created by Steffca A/S and includes copyrighted material, trademarks and other proprietary information owned by Steffca A/S. All rights reserved.

Steffca A/S can accept no responsibility for possible errors in manuals, brochures and catalogues. All information and specifications are for information only and are subject to change without notice. Steffca A/S reserves the right to modify its products without prior notice, including already ordered products, if this can occur without changing already stated specifications.