



PRODUCT INFORMATION

# REVOSEAL JP1 & JP2 GASKETS

## BENEFITS

Revo seal JP is high-quality and advanced technology gaskets, used where standard gaskets will be insufficient.

Revo seal gaskets stand out by having the lowest leak rate of all gaskets available on the market.

They are based on metal-to-metal technology. Enclosing the graphite removes the oxygen, allowing the gasket to withstand up to 1,000°C.

The design of the gasket prevents the graphite from sticking to the flange. JP2 is especially recommended for pressures higher than 200 bar and temperatures above 500°C.

These gaskets are also available in PTFE version with EC1935-2004 for food production.

Revo seal gaskets are used in the following industries: oil and gas, chemical, petrochemical, food and pharmaceutical.

## MATERIALS

- Stainless steel 316Ti
- Graphite (also available with PTFE for food)

## SPECIFICATION

<b>Temperature</b>	-200°C - 1000°C
<b>Pressure</b>	From vacuum to 400 bar
<b>Thickness</b>	4.2 mm (+/- 0.1 mm)
<b>Fireproof certificate</b>	API 607 (also for PTFE)
<b>Firesafe</b>	VDI 2200
<b>TA Air</b>	VDI 2290 – DIN EN 1591

## USES

